

700 Series Pop-Up

FEATURES

- Heavy duty internally supported wiper seal
- Patented lateral discharging flush plug
- High impact virgin ABS plastic construction of body, piston, and cap
- Stainless steel retraction spring
- Spring-loaded ratchet on all models for directional adjustment of spray pattern
- Easy service from top of head
- Available with female (red flush plug) or male (green flush plug) threaded pistons

OPERATING SPECIFICATIONS

- Operating pressure: 15-70 PSI
- Recommended working pressure: 30 PSI

DIMENSIONS

- 1/2" female pipe thread on bottom inlet
- Male threaded piston to accept fixed or adjustable arc nozzles with female threads
- Female threaded piston to accept fixed or adjustable arc nozzles with male threads



702

Body Height: 4"
Pop-Up Height: 2"
Exposed Surface Diameter: 2"



703

Body Height: 5"
Pop-Up Height: 3"
Exposed Surface Diameter: 2"



704

Body Height: 6"
Pop-Up Height: 4"
Exposed Surface Diameter: 2"



706

Body Height: 8"
Pop-Up Height: 6"
Exposed Surface Diameter: 2"



712

Body Height: 15 1/2"
Pop-Up Height: 12"
Exposed Surface Diameter: 2 1/8"
• Side Inlet

OPTIONS AVAILABLE

- Check Valve (CKV)
- Reclaimed purple cap

ORDER SPECIFICATION GUIDE : Model(Option1) + Option2 + Option3

Model	Option 1	Option 2	Option 3
702 = 2" Pop-Up	Blank = Male F = Female	Blank = No Option -CKV = Check Valve	Blank = Black Cap -R = Reclaimed Purple Cap
703 = 3" Pop-Up			
704 = 4" Pop-Up			
705 = 5" Pop-Up			
706 = 6" Pop-Up			
712 = 12" Pop-Up			

Examples

- 702F = 2" Female Pop-up only
- 704 - CKV = 4" Male Pop-Up with a Check Valve
- 712F - R = 12" Female Pop-Up with a Purple Cap

